GLASS DOOR MERCHANDISER REFRIGERATOR

Sliding Doors


EM – Series Model: EMGR48 | EMGR48B





















Please visit our website for updated Energy Efficiency information.

Cabinet Construction

Heavy duty white coated steel for cabinet interior and exterior. High quality stainless steel interior floor with round edges for convenient cleaning. ABS evaporator drain cover. 2.5" thick high density foamed-in-place polyurethane insulation. Adjustable screw legs for leveling.

Refrigeration System

- · Bottom mounted condensing unit
- · Removable bottom grill and slide-out condensing unit for easy repair and maintenance
- Oversized condenser and evaporator coils quickly achieve and maintain desired temperature
- Forced-air cooling with oversized evaporator fan motors providing balanced airflow throughout cabinet to ensure faster temperature drop
- · Environmentally friendly CFC free R-134A refrigerant
- · Air defrost controlled by thermostat
- · Copper tube and aluminum fin evaporator with anti-corrosive coating
- · Energy efficient condensate drain pan with wicking pads
- · Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P

Doors

- · Black PVC door frames
- Low emissivity double pane glass system reflects UV rays and improves insulation for maximized energy efficiency
- · Automatic self-close by weight
- · Removable doors and stainless steel door tracks for easy cleaning

Lighting

 Shielded vertical LED interior lighting with on/off switch for energy saving, less heat generation and enhanced illumination (available from 2015 models)

Shelving

- · Four epoxy coated wire shelves per section
- · Stainless steel pilasters and shelf clips

Temperature Control

- · Factory preset temperature, 35°F
- · Temperature setting range from 32°F to 42°F
- · Easy to set thermostat dial

Option

· 2 1/2" and 4" diameter casters (3 1/2" and 5" overall height)

Model	# of	Capacity	НР	Refrigerant	# of	Capacity 20 oz.	Power	Amps	Crated Weight	Ext	terior Dimens	ions
Model	Doors	(Cu. Ft.)		Honigorani	Shelves	Bottles	(V-Hz-Ph)	Allipa	Grateu Weight	L	D	Н
EMGR48 EMGR48B	2	48	1/2+	R-134A	8	448	115-60-1	10.40	520lbs (235.9kg)	53 1/8" (1350 mm)	30 3/4" (780 mm)	78 7/8" (2005 mm)

Specifications subject to change without notice.


GLASS DOOR MERCHANDISER REFRIGERATOR

Sliding Doors


EM - Series Model: EMGR48 I EMGR48B




Net capaci	ty cu. ft.	48 (1359.2 cu l)			
	Length Overall in.	53 1/8" (1350)			
Exterior (mm)	Depth Overall in.	30 3/4" (780)			
	Height Overall in.	78 7/8" (2005)			
Crated Wei	ght	520lbs (235.9kg)			
# of Doors		2 (Sliding Door)			
# of Shelves Capacity 20oz. Bottles		8			
Capacity 2	Ooz. Bottles	448			
Shelf Size Length x Depth in. (mm)		24 1/4" x 23 5/8" (615 x 600)			
ELECTRI	CAL DATA				
Voltage (V-	Hz-Ph)	115-60-1 10.40			
Full load ar	nperes				
Feed wires	with Ground	3			
Cord Lengt	h ft.	9			
REFRIGE	RATION DATA				
Refrigerant		R-134A 1/2+ HP			
Compresso	or H.P.				
BTU/HR ^a	(Kcal/h)	3968 (1000)			



a: Based on evaporating temperature of 23°F(-5°C) & Condensing temperature of 131°F(55°C).




Dimensions inches (mm)



Front View

Side View



Top View